

## PREMIER ACRYLIC MATT AND SHEEN EMULSION

### PRODUCT DESCRIPTION

Premium quality matt and sheen emulsion for both trade and DIY use, based on an acrylic polymer. Washability and excellent dirt resistance are built in, with extenders and pigments to give a non toxic, high covering finish.

### USES

For painting all interior surfaces, including high humidity areas such as kitchens and bathrooms. Ideal for plasterboard, brick, hardboard, embossed paper and textured coatings.

### TECHNICAL PROPERTIES

<b>Colour</b>	White, Magnolia, colours to order	
<b>Finish</b>	Matt or Sheen	
	Matt	Sheen
<b>Specific Gravity</b>	1.326	1.217
<b>Volume Solids</b>	28%	23%
<b>Recommended Film Thickness</b>	90µm WFT / 25µm DFT	106µm WFT / 25µm DFT
<b>Theoretical Spreading Rate</b>	11 m <sup>2</sup> /litre	9 m <sup>2</sup> /litre
<b>Application Method</b>	Brush, Roller	
<b>VOC</b>	<5 g/litre	
		80 g/litre
<b>Drying Times</b>	<b>10°C</b>	<b>20°C</b>
Touch Dry	45 minutes	30 minutes
Hard Dry	3 hours	2 hours
Minimum Overcoat	3 hours	2 hours
Maximum Overcoat	Indefinite	Indefinite
	Dry times will be extended at lower temperatures.	

### CERTIFICATION/APPROVALS

#### RECOMMENDED SYSTEMS

Aquabond Acrylic Sealer, Stormcote Stabilising Sealer

### SURFACE PREPARATION

Ensure surfaces are clean, dry and free from dirt, grease and other contamination. Fill all holes with a suitable filler.  
On porous surfaces coat with Aquabond Acrylic Sealer or if necessary use Stormcote Stabilising Sealer.

## PRODUCT APPLICATION

<b>Mixing</b>	If necessary, stir well before use.
<b>Thinners</b>	Water
<b>Brush</b>	Do not thin.
<b>Roller</b>	Do not thin.
<b>Conventional Spray</b>	Not suitable.
<b>Airless Spray</b>	Not suitable.
<b>Air Assisted Airless Spray</b>	Not suitable.
<b>Cleaner</b>	Water
<b>Cleanup Considerations</b>	All equipment should be cleaned immediately after use with Water. It is advisable that equipment should be cleaned/flushed during the course of application, the frequency of which will depend on the volume of material used and timescale over which applied. Ensure all waste materials (including packaging) are disposed of in accordance with local regulations.

## HEALTH, SAFETY & ENVIRONMENTAL

This product must be used in accordance with the Material Safety Data Sheet supplied by Spencer Coatings Limited. The user must observe local health, safety and environmental regulations when using this product. Consult Spencer Coatings Limited if there are any concerns over the suitability of this product.

## PACK SIZES

5 litre and 10 litre

## PACK WEIGHTS

5 litre: 7 kg.  
10 litre: 14 kg.

## STORAGE CONDITIONS

**PROTECT FROM FROST AND STORE ABOVE 5°C. ENSURE STRICT STOCK ROTATION IS PRACTISED.**

## LIMITATIONS

Do not apply below 5°C.

## DISCLAIMER

The information given in these specifications and technical advice - whether verbal, or in writing or by way of trials is for guidance only and is given in good faith, but without warranty. This also applies where proprietary rights or third parties are involved. Any person using Spencer products without first making further enquiries as to the suitability of the products for the intended purpose and testing the products to assess their fitness for the purpose does so at their own risk. The application, use and processing of the products are beyond our control and are therefore your own responsibility, and we can accept no liability for the performance of the products arising out of such use, beyond the value of the goods delivered by us. The information contained in these data sheets is liable to modification from time to time in the light of experience and our policy of continuous development.

It is the user's responsibility to ensure that this sheet is current prior to using the product.