

SHELLAC CLEAR VARNISH

PRODUCT DESCRIPTION

Shellac Clear Varnish is pure shellac solution in alcohol conforming to BS 1284 for high quality varnishing of furniture.

USES

Shellac Clear Varnish can be used where maximum non-yellowing characteristics are required, being a pure lightly coloured resin solution and is a traditional product for furniture coatings.

TECHNICAL PROPERTIES

Colour	Clear		
Finish	Glossy		
Curing Agent	-		
Mix Ratio	-		
Specific Gravity	0.91		
Weight Solids	26%		
Recommended Film Thickness	-		
Theoretical Spreading Rate	7-10 m ² /litre (depends on wood type)		
Application Method	Brush, Cloth.		
Flash Point	12°C		
VOC	680 g/litre		
Drying Times	10°C	20°C	30°C
Touch Dry	30 minutes	10 minutes	5 minutes
Hard Dry	40 minutes	20 minutes	15 minutes
Minimum Overcoat	50 minutes	30 minutes	25 minutes
Maximum Overcoat	Indefinite	Indefinite	Indefinite

CERTIFICATION/APPROVALS

RECOMMENDED SYSTEMS

Shellac Knotting, Shellac Sanding Sealer

SURFACE PREPARATION

Ensure surfaces are clean, dry and free from dirt, grease and other contamination.

Knots should be sealed using Shellac Knotting.

On new wood a coat of Shellac Sanding Sealer is recommended.

PRODUCT APPLICATION

Mixing	Ready for use but stir well to ensure consistency.
Thinners	Do not thin.
Brush	Apply unthinned by brush or by traditional French polish techniques.
Cloth	Apply unthinned by brush or by traditional French polish techniques.
Conventional Spray	-
Airless Spray	-
Air Assisted Airless Spray	-
Cleaner	Thinner No.5
Cleanup Considerations	All equipment should be cleaned immediately after use with Thinner No.5 It is advisable that equipment should be cleaned/flushed during the course of application, the frequency of which will depend on the volume of material used and timescale over which applied. Ensure all waste materials (including packaging) are disposed of in accordance with local regulations.

HEALTH, SAFETY & ENVIRONMENTAL

This product must be used in accordance with the Material Safety Data Sheet supplied by Spencer Coatings Limited. The user must observe local health, safety and environmental regulations when using this product. Consult Spencer Coatings Limited if there are any concerns over the suitability of this product.

PACK SIZES

2.5 litre

PACK WEIGHTS

2.5 litre : 2.28 kg.

STORAGE CONDITIONS

Store away from high temperatures and direct heat.

LIMITATIONS

Non specific.

DISCLAIMER

The information given in these specifications and technical advice - whether verbal, or in writing or by way of trials is for guidance only and is given in good faith, but without warranty. This also applies where proprietary rights or third parties are involved. Any person using Spencer products without first making further enquiries as to the suitability of the products for the intended purpose and testing the products to assess their fitness for the purpose does so at their own risk. The application, use and processing of the products are beyond our control and are therefore your own responsibility, and we can accept no liability for the performance of the products arising out of such use, beyond the value of the goods delivered by us. The information contained in these data sheets is liable to modification from time to time in the light of experience and our policy of continuous development.

It is the user's responsibility to ensure that this sheet is current prior to using the product.