

## SHELLAC SANDING SEALER

### PRODUCT DESCRIPTION

Shellac Sanding Sealer is a shellac solution in alcohols for sealing and priming wood.

### USES

Specially formulated to provide a quick drying and easily sanded primer for wood for interior use. When dry it sands easily without clogging the paper and provides an excellent smooth base for polishing or brush coating, reducing sinking of the final coats.

### TECHNICAL PROPERTIES

<b>Colour</b>	Clear		
<b>Finish</b>	Glossy		
<b>Curing Agent</b>	-		
<b>Mix Ratio</b>	-		
<b>Specific Gravity</b>	1.00		
<b>Weight Solids</b>	40%		
<b>Recommended Film Thickness</b>	-		
<b>Theoretical Spreading Rate</b>	7-10 m <sup>2</sup> /litre (depends on wood type)		
<b>Application Method</b>	Brush, Cloth, Spray		
<b>Flash Point</b>	12°C		
<b>VOC</b>	600 g/litre		
<b>Drying Times</b>	<b>10°C</b>	<b>20°C</b>	<b>30°C</b>
Touch Dry	30 minutes	10 minutes	5 minutes
Hard Dry	40 minutes	20 minutes	15 minutes
Minimum Overcoat	50 minutes	30 minutes	25 minutes
Maximum Overcoat	Indefinite	Indefinite	Indefinite

### CERTIFICATION/APPROVALS

**RECOMMENDED SYSTEMS** Shellac Knotting, Stripkwik

### SURFACE PREPARATION

Ensure surfaces are clean, dry and free from dirt, grease and other contamination.

Knots should be sealed using Shellac Knotting prior to applying Sanding Sealer.

Stripkwik Paint Remover should be used to prepare old painted surfaces.

## PRODUCT APPLICATION

<b>Mixing</b>	Stir well before use.
<b>Thinners</b>	SP Thinner
<b>Brush</b>	Add SP Thinner if necessary to adjust the consistency. Apply with brush or by traditional French polish techniques.
<b>Cloth</b>	Add SP Thinner if necessary to adjust the consistency. Apply with brush or by traditional French polish techniques.
<b>Conventional Spray</b>	Add SP Thinner if necessary to adjust the consistency. Use 30-40 psi pressure and 1.4-1.8 diameter nozzle.
<b>Airless Spray</b>	-
<b>Air Assisted Airless Spray</b>	-
<b>Cleaner</b>	SP Thinner
<b>Cleanup Considerations</b>	All equipment should be cleaned immediately after use with SP Thinner. It is advisable that equipment should be cleaned/flushed during the course of application, the frequency of which will depend on the volume of material used and timescale over which applied. Ensure all waste materials (including packaging) are disposed of in accordance with local regulations.

## HEALTH, SAFETY & ENVIRONMENTAL

This product must be used in accordance with the Material Safety Data Sheet supplied by Spencer Coatings Limited.  
The user must observe local health, safety and environmental regulations when using this product.  
Consult Spencer Coatings Limited if there are any concerns over the suitability of this product.

## PACK SIZES

2.5 litre

## PACK WEIGHTS

2.5 litre : 2.5 kg.

## STORAGE CONDITIONS

Store away from high temperatures and direct heat.

## LIMITATIONS

Excessively thick coats should be avoided.

## DISCLAIMER

The information given in these specifications and technical advice - whether verbal, or in writing or by way of trials is for guidance only and is given in good faith, but without warranty. This also applies where proprietary rights or third parties are involved. Any person using Spencer products without first making further enquiries as to the suitability of the products for the intended purpose and testing the products to assess their fitness for the purpose does so at their own risk. The application, use and processing of the products are beyond our control and are therefore your own responsibility, and we can accept no liability for the performance of the products arising out of such use, beyond the value of the goods delivered by us. The information contained in these data sheets is liable to modification from time to time in the light of experience and our policy of continuous development.

It is the user's responsibility to ensure that this sheet is current prior to using the product.