

TIMBERCOAT 1 FENCEGUARD

PRODUCT DESCRIPTION

A low build water based creosote replacement wood treatment. This product is microporous, harmless to plants and animal life and offers good protection against water, sunlight and fungal attack. Penetrates deeply into wood but the spreading rates are noticeably higher than creosote, giving a cost effective advantage.

USES

On fences, sheds, rough and smooth sawn softwood and old weathered creosote painted surfaces.

TECHNICAL PROPERTIES

Colour	Dark Oak, Cedar, Golden Brown		
Finish	Semi Opaque, Slight Sheen		
Curing Agent	-		
Mix Ratio	-		
Specific Gravity	1.008		
Volume Solids	5%		
Recommended Film Thickness	-		
Theoretical Spreading Rate	4-8 m ² /litre (depends on wood type)		
Application Method	Brush, Roller		
Flash Point	-		
VOC	50 g/litre		
Drying Times	10°C	20°C	30°C
Touch Dry	6 hours	4 hours	2 hours
Hard Dry	8 hours	6 hours	4 hours
Minimum Overcoat	8 hours	6 hours	4 hours
Maximum Overcoat	Indefinite	Indefinite	Indefinite

CERTIFICATION/APPROVALS

RECOMMENDED SYSTEMS

Stormcote Fungicidal Treatment, Stripkwik

SURFACE PREPARATION

Timber should be clean and dry before application. Remove any contamination such as lichens, moss or fungi with a wire brush. If contamination is heavy, treat with Stormcote Fungicidal Treatment and allow to dry before painting. Old varnish/painted surfaces must be stripped with a paint remover i.e. Stripkwik before treatment.

PRODUCT APPLICATION

Mixing	Stir thoroughly before use.
Thinners	Do not thin.
Brush	Stir well before use then brush liberally over the surface working from top to bottom. For extra protection or a deeper colour, apply a second coat after the first coat has dried. Fenceguard can be applied to old weathered creosote surfaces successfully. Wash any splashes off plants immediately to avoid staining. Full protection will only be obtained when the coating has fully dried and application should not be carried out externally if there is any chance of adverse weather conditions.
Roller	Stir well before use then brush liberally over the surface working from top to bottom. For extra protection or a deeper colour, apply a second coat after the first coat has dried. Fenceguard can be applied to old weathered creosote surfaces successfully. Wash any splashes off plants immediately to avoid staining. Full protection will only be obtained when the coating has fully dried and application should not be carried out externally if there is any chance of adverse weather conditions.
Cleaner	Warm Soapy Water.
Cleanup Considerations	All equipment should be cleaned immediately after use with Water. It is advisable that equipment should be cleaned/flushed during the course of application, the frequency of which will depend on the volume of material used and timescale over which applied. Ensure all waste materials (including packaging) are disposed of in accordance with local regulations.

HEALTH, SAFETY & ENVIRONMENTAL

This product must be used in accordance with the Material Safety Data Sheet supplied by Spencer Coatings Limited. The user must observe local health, safety and environmental regulations when using this product. Consult Spencer Coatings Limited if there are any concerns over the suitability of this product.

PACK SIZES

5 litre

PACK WEIGHTS

5 litre : 5 kg.

STORAGE CONDITIONS

PROTECT FROM FROST AND STORE ABOVE 5°C. ENSURE STRICT STOCK ROTATION IS PRACTISED.

LIMITATIONS

Do not apply in poor drying conditions or when there is the likelihood of rain.
Best applied in warm and dry conditions.

DISCLAIMER

The information given in these specifications and technical advice - whether verbal, or in writing or by way of trials is for guidance only and is given in good faith, but without warranty. This also applies where proprietary rights or third parties are involved. Any person using Spencer products without first making further enquiries as to the suitability of the products for the intended purpose and testing the products to assess their fitness for the purpose does so at their own risk. The application, use and processing of the products are beyond our control and are therefore your own responsibility, and we can accept no liability for the performance of the products arising out of such use, beyond the value of the goods delivered by us. The information contained in these data sheets is liable to modification from time to time in the light of experience and our policy of continuous development.

It is the user's responsibility to ensure that this sheet is current prior to using the product.