

Reference: 06FET
Issue Number: 0
Issue Date: November 2002
Supersedes Issue: -

FLOORCOTE ETCH TREATMENT

PRODUCT DESCRIPTION

A Hydrochloric Acid based solution designed to open up dense concrete, neutralise newly laid concrete and remove surface laitance quickly.

USES

Application to floors which are too hard, highly alkaline, granolithic or coated with surface laitance (soft weak surface layer).

TECHNICAL PROPERTIES

Colour	Clear Solution		
Finish			
Curing Agent			
Mix Ratio			
Specific Gravity	1.08		
Volume Solids			
Recommended Film Thickness			
Theoretical Spreading Rate	5 m ² /litre (varies with substrate)		
Application Method	Brush		
Flash Point			
VOC			
Drying Times	10°C	20°C	30°C
Touch Dry			
Hard Dry			
Minimum Overcoat			
Maximum Overcoat			

CERTIFICATION/APPROVALS

RECOMMENDED SYSTEMS All Floorcote Products

SURFACE PREPARATION

If surface is porous or very dry, dampen prior to application of the product.

PRODUCT APPLICATION

Mixing	Ready for use.
Thinners	
Brush	Application for all surfaces : brush product into surface and allow to react for 15 minutes. Hose off and allow to dry.
Roller	
Conventional Spray	
Airless Spray	
Air Assisted Airless Spray	
Cleaner	Water
Cleanup Considerations	All equipment should be cleaned immediately after use with water. It is advisable that equipment should be cleaned/flushed during the course of application, the frequency of which will depend on the volume of material used and timescale over which applied. Ensure all waste materials (including packaging) are disposed of in accordance with local regulations.

HEALTH, SAFETY & ENVIRONMENTAL

This product must be used in accordance with the Material Safety Data Sheet supplied by Spencer Coatings Limited. The user must observe local health, safety and environmental regulations when using this product. Consult Spencer Coatings Limited if there are any concerns over the suitability of this product.

PACK SIZES

5 litre.

PACK WEIGHTS

5 litre: 5.4 Kg.

STORAGE CONDITIONS

Protect from frost.

LIMITATIONS

After treatment any soluble salts and emulsified oil and dirt must be completely removed before painting. When using Etch Treatment avoid spilling onto any machinery and protect machinery from fumes.

DISCLAIMER

The information given in these specifications and technical advice - whether verbal, or in writing or by way of trials is for guidance only and is given in good faith, but without warranty. This also applies where proprietary rights or third parties are involved. Any person using Spencer products without first making further enquiries as to the suitability of the products for the intended purpose and testing the products to assess their fitness for the purpose does so at their own risk. The application, use and processing of the products are beyond our control and are therefore your own responsibility, and we can accept no liability for the performance of the products arising out of such use, beyond the value of the goods delivered by us. The information contained in these data sheets is liable to modification from time to time in the light of experience and our policy of continuous development.

It is the user's responsibility to ensure that this sheet is current prior to using the product.